


EC TYPE-EXAMINATION CERTIFICATE

according to Marine Equipment Directive (Module B)



NOTIFIED BODY 0809

This is to certify that VTT Expert Services Ltd did undertake the relevant type approval procedures for the type of equipment identified below which was found to be in compliance with the requirements of Marine Equipment Directive (MED) 2014/90/EU, subject to any conditions in the schedule attached hereto.

Merit Jahti 20

meet the requirements imposed in IMO 2010 FTP Code (ref. Ch. 5.2.1 and Ch. 8), Annex 1 Part 2 and Part 5 (IMO Resolution MSC.307(88) Annex 1 Part 2 and Part 5) on

materials with low flame-spread characteristics and not producing excessive quantities of smoke and toxic products or not giving rise to toxic hazards at elevated temperatures

and the provisions of Marine Equipment Directive 2014/90/EU, that apply to

surface materials with low flame-spread characteristics.

These products have been assigned a U.S. Coast Guard Module B number (**164.112 / EC0809**) to note type approval to Module B only as it pertains to obtaining U.S. Coast Guard approval as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment" signed February 27th, 2004.

Manufacturer of the product is

Tikkurila Oyj

The Certificate is valid until March 27, 2022 unless suspended, expired or withdrawn, provided the conditions in this certificate are complied with and the equipment remains satisfactory in service.

Espoo March 28, 2017

Tiina Ala-Outinen
Business Manager



Heli Välimäki
Senior Expert

Manufacturer	Tikkurila Oyj Kuninkaalantie 1 FI-01301 Vantaa Finland
Regulation Item	Annex A.1 Item No A.1/3.18b, surface materials with low flame-spread characteristics.
Products	Merit Jahti 20, colour clear.
Product description	One component urethane alkyd lacquer.
Approved application	On any metallic substrate with a thickness of 0.525 mm or higher or on non-metallic, non-combustible substrates with a density of 950 kg/m ³ or higher and a thickness of 25 mm or greater. Dry film thickness of the paint max. 40 µm.
Technical document	Product Data Sheet of Tikkurila Oyj, November 5, 2015.
Test reports	Test Report VTT-S-01195-17, March 9, 2017, VTT Expert Services Ltd. Test Report VTT-S-01196-17, March 9, 2017, VTT Expert Services Ltd.
Test methods and standard	IMO FTPC Part 5 (IMO Resolution MSC. 61(67) Annex 1 Part 5) Test for surface flammability (test procedure IMO Resolution A.653(16)).
Notes	<p>This certificate replaces the previous EC Type-Examination Certificates (B-module) VTT-C-11980-15-17.</p> <p>This certificate will not be valid if the manufacturer makes any changes or modifications to the approved type of equipment, which have not been notified to, and agreed with the notified body named on this certificate.</p> <p>Should the specified regulations or standards be amended during the period of validity of this certificate, the product is to be reapproved prior to it being placed on the market and on board vessels to which the amended regulations or standards apply.</p> <p>The Mark of Conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-control phase module (D, E or F) of Annex B of the Directive is fully complied with and controlled by a written inspection agreement with a notified body.</p>

END OF CERTIFICATE

