



# Colowood

## DESCRIPTION

A water-borne filler for wooden surfaces.

## PRODUCT FEATURES AND RECOMMENDED USES

- For filling holes in interior wooden surfaces such as fibre boards, solid wood or veneer
- Recommended for furniture, doors, panel walls and ceilings

## TECHNICAL DATA

### Volume solids

64±2%

### Weight solids

82±2%

### Specific gravity

2,0 ± 0,2 kg/l

### Recommended spreading amounts and theoretical coverage

Practical coverage depends on the application method, conditions and the shape and roughness of the surface to be treated.

### Drying times

Thin filling layer can be sanded after 4 hours and deeper filling layer after 24 hours.

### Gloss

Matt.

### Color shades

Birch, birch knot, pine, pine knot, oak, oak knot, beech, white and mahogany



# Colowood

## APPLICATION INSTRUCTIONS

<b>Surface preparation</b>	Remove dust, loose particles and other impurities from the surface.
<b>Recommended topcoats</b>	Can be recoated with Tikkurila's water-borne, water-borne UV and solvent-borne products.
<b>Application conditions</b>	The surface to be treated must be dry, the temperature of the air at least +5°C and the relative humidity of the air below 80%.
<b>Application</b>	Apply with a spatula. Thin with water, if necessary. Fill large holes preferably twice or several times. Sand the surface and remove sanding dust.
<b>Thinners</b>	Water
<b>Cleaning of equipment</b>	Water.
<b>VOC</b>	The Volatile Organic Compounds amount is 21 g/litre of putty. VOC content of the putty (thinned 10 % by volume) is 20 g/l.

**HEALTH AND SAFETY** Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets.  
A health and safety data sheet is available on request from Tikkurila Oyj.

### **For industrial and professional use only.**

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

The product is intended for professional use only and shall only be used by professionals who have sufficient knowledge and expertise on the proper use of the product. The information above is advisory only. To the extent permitted by applicable law, we shall not approve of any liability for the conditions under which the product is being used or for the use or application of the product.

In case you intend to use the product for any other purpose than that recommended in this document without first getting our written confirmation on the suitability for the intended use, such use takes place at your own risk.