



# PINJADUR

Water-borne polyurethane paints for exterior doors and windows

**Pinjadur paints are** innovative water-borne polyurethane paints developed for exterior windows, doors and fiber cement surfaces. These paints can also be used for interior doors, kitchen and bathroom cabinets etc. Thanks to their eco-friendly properties, Pinjadur paints are in high demand on the market. They form a durable finish with outstanding color and gloss retention, even in Scandinavia's harsh weather conditions.

- A durable, easy to clean and non-chalking topcoat
- Excellent gloss and color retention in climatic stress
- Can be cured at higher temperatures.





# PINJADUR

## Water-borne polyurethane paints for exterior doors and windows

### PRODUCT INFORMATION

Following extensive product development, Tikkurila has created a water-borne, two-component polyurethane paint system, which provides excellent durability comparable with that of a solvent-borne polyurethane system. This system, which consists of a primer Pinjadur Primer and a semi-matt topcoat Pinjadur 30, provides door and window surfaces with excellent resistance to outdoor exposure. It has been tested in accordance with the EN927 standard.

**Pinjadur Primer** is a water-borne, two-component polyurethane primer for interior and exterior applications. It is a fast-drying, easy-to-sand and flexible primer that has good filling properties. The paint ensures minimal swelling of wood and mdf- and hdf-board fibers. Pinjadur Primer has an excellent ability to slow the discoloration of the topcoat caused by resins.

**Code:** 006 5007

**Color:** White.

**Pinjadur 30** is a two-component, water-borne polyurethane topcoat. This semi-matt finish is designed for interior and exterior applications. It is particularly recommended for fiber cement flat sheet and wooden surfaces in exterior premises. The product forms a durable, easy-to-clean and non-chalking finish with excellent gloss and color retention. Pinjadur 30 is tintable in various colors with the Temaspeed Fonte tinting system.

**Code:** 33V -series

**Colors:** Temaspeed Fonte tinting system.

### TYPICAL PAINT SYSTEMS

#### WW75

Treatment	Product	Application	Amount wet film, g/m <sup>2</sup>
Priming	1-2 x Pinjadur Primer	Spraying	100-150
Topcoating	1 x Pinjadur 30	Spraying	80-150



### YOUR TRUSTWORTHY PARTNER IN INDUSTRIAL PAINTING

Tikkurila's experienced staff will be delighted to provide you with full details on coating specifications, help in calculating of film thicknesses, as well as assisting in painting processes and inspections. Please contact our technical group staff by phone: **+358201912098** or by e-mail: **info.coatings@tikkurila.com**

Tikkurila Oyj  
P.O. Box 53, FI-01301 Vantaa, Finland  
Tel. +358 20 191 2000  
info.coatings@tikkurila.com | www.tikkurila.com/industry

